

Enclosed KTU7 Circuit Breaker - Type 4 / 4X / 12

Fixed Thermal Current Rating [A]		Magnetic Trip [A]	Interrupting Rating (60Hz) [KA]			Catalog Number	Price	Dimension Code
			240V	480Y /277V	600Y /347V			
KTU7-D — High Interrupting Capacity – 2-Pole								
0.5	15...20xIn		100	100	50	KTU7-D-2D-0.5-VG	775 Q6 ①	
1.0	15...20xIn		100	100	50	KTU7-D-2D-1-VG		
2.0	15...20xIn		100	100	50	KTU7-D-2D-2-VG		
3.0	15...20xIn		100	100	50	KTU7-D-2D-3-VG		
4.0	15...20xIn		100	100	50	KTU7-D-2D-4-VG		
5.0	15...20xIn		100	100	50	KTU7-D-2D-5-VG		
6.0	15...20xIn		100	100	50	KTU7-D-2D-6-VG		
8.0	15...20xIn		100	100	50	KTU7-D-2D-8-VG		
10.0	15...20xIn		100	100	50	KTU7-D-2D-10-VG		
12.0	15...20xIn		65	65	25	KTU7-D-2D-12-VG		
15.0	15...20xIn		65	65	25	KTU7-D-2D-15-VG		
20.0	15...20xIn		65	65	25	KTU7-D-2D-20-VG		
25.0	15...20xIn		65	65	25	KTU7-D-2D-25-VG		
30.0	15...20xIn		65	65	25	KTU7-D-2D-30-VG		
KTU7-D — High Interrupting Capacity – 3-Pole								
0.5	15...20xIn		100	100	50	KTU7-D-3D-0.5-VG	875 Q6 ①	
1.0	15...20xIn		100	100	50	KTU7-D-3D-1-VG		
2.0	15...20xIn		100	100	50	KTU7-D-3D-2-VG		
3.0	15...20xIn		100	100	50	KTU7-D-3D-3-VG		
4.0	15...20xIn		100	100	50	KTU7-D-3D-4-VG		
5.0	15...20xIn		100	100	50	KTU7-D-3D-5-VG		
6.0	15...20xIn		100	100	50	KTU7-D-3D-6-VG		
8.0	15...20xIn		100	100	50	KTU7-D-3D-8-VG		
10.0	15...20xIn		100	100	50	KTU7-D-3D-10-VG		
12.0	15...20xIn		65	65	25	KTU7-D-3D-12-VG		
15.0	15...20xIn		65	65	25	KTU7-D-3D-15-VG		
20.0	15...20xIn		65	65	25	KTU7-D-3D-20-VG		
25.0	15...20xIn		65	65	25	KTU7-D-3D-25-VG		
30.0	15...20xIn		65	65	25	KTU7-D-3D-30-VG		

Non-metallic, Type 4 / 4X / 12 Enclosure



Includes:

- Type 4 / 4X / 12 enclosure – watertight, dust-tight, corrosion resistant
- KTU7 UL489 Molded Case Circuit Breaker
- Black Type 4/4X/12; IP66 handle (Cat.# KT7-HTN Series E) ②

Modifications (Factory Assembled) ③

Description	Add Suffix to Cat. Number	Price Adder
KT7 Auxiliaries & Trip Contacts - Front Mount		
1 NO Auxiliary	-A10	60
1 NC Auxiliary	-A01	
1 NO + 1 NC Auxiliary	-A11	
2 NO Auxiliaries	-A20	
1 NO SC+OL + 1 NC Auxiliary	-T10A01	90
1 NO SC+OL + 1 NO Auxiliary	-T10A10	

① KTU7 is 80% rated in this enclosure.

② A red and yellow handle may be selected instead of the standard black handle. Change "VG" suffix to "VJ". Ex: Change KTU7-D-2D-0.16-VG to KTU7-D-2D-0.16-VJ.

③ Load Terminal Cover KT7-PEFC is included with any factory modifications.

Enclosed KTU7 Circuit Breaker - Type 12

Fixed Thermal Current Rating [A]		Magnetic Trip [A]	Interrupting Rating (60Hz) [KA]			Catalog Number	Price	Dimension Code
			240V	480Y /277V	600Y /347V			
KTU7-D — High Interrupting Capacity – 2-Pole								
0.5	15...20xln	100	100	50	KTU7-D-2D-0.5-DG	810	L ①	
1.0	15...20xln	100	100	50	KTU7-D-2D-1-DG			
2.0	15...20xln	100	100	50	KTU7-D-2D-2-DG			
3.0	15...20xln	100	100	50	KTU7-D-2D-3-DG			
4.0	15...20xln	100	100	50	KTU7-D-2D-4-DG			
5.0	15...20xln	100	100	50	KTU7-D-2D-5-DG			
6.0	15...20xln	100	100	50	KTU7-D-2D-6-DG			
8.0	15...20xln	100	100	50	KTU7-D-2D-8-DG			
10.0	15...20xln	100	100	50	KTU7-D-2D-10-DG			
12.0	15...20xln	65	65	25	KTU7-D-2D-12-DG			
15.0	15...20xln	65	65	25	KTU7-D-2D-15-DG			
20.0	15...20xln	65	65	25	KTU7-D-2D-20-DG			
25.0	15...20xln	65	65	25	KTU7-D-2D-25-DG			
30.0	15...20xln	65	65	25	KTU7-D-2D-30-DG			
KTU7-D — High Interrupting Capacity – 3-Pole								
0.5	15...20xln	100	100	50	KTU7-D-3D-0.5-DG	910	L ①	
1.0	15...20xln	100	100	50	KTU7-D-3D-1-DG			
2.0	15...20xln	100	100	50	KTU7-D-3D-2-DG			
3.0	15...20xln	100	100	50	KTU7-D-3D-3-DG			
4.0	15...20xln	100	100	50	KTU7-D-3D-4-DG			
5.0	15...20xln	100	100	50	KTU7-D-3D-5-DG			
6.0	15...20xln	100	100	50	KTU7-D-3D-6-DG			
8.0	15...20xln	100	100	50	KTU7-D-3D-8-DG			
10.0	15...20xln	100	100	50	KTU7-D-3D-10-DG			
12.0	15...20xln	65	65	25	KTU7-D-3D-12-DG			
15.0	15...20xln	65	65	25	KTU7-D-3D-15-DG			
20.0	15...20xln	65	65	25	KTU7-D-3D-20-DG			
25.0	15...20xln	65	65	25	KTU7-D-3D-25-DG			
30.0	15...20xln	65	65	25	KTU7-D-3D-30-DG			

Painted Steel, Type 12 Enclosure



Includes:

- Type 12 enclosure – dusttight
- KTU7 UL489 Molded Case Circuit Breaker
- Black Type 4/4X/12; IP66 handle (Cat.# KT7-HTN Series E) ②

Modifications (Factory Assembled) ③

Description	Add Suffix to Cat. Number	Price Adder
KT7 Auxiliaries & Trip Contacts - Front Mount		
1 NO Auxiliary	-A10	60
1 NC Auxiliary	-A01	
1 NO + 1 NC Auxiliary	-A11	
2 NO Auxiliaries	-A20	
1 NO SC+OL + 1 NC Auxiliary	-T10A01	90
1 NO SC+OL + 1 NO Auxiliary	-T10A10	

① KTU7 is 80% rated in this enclosure.
 ② A red and yellow handle may be selected instead of the standard black handle. Change “DG” suffix to “DJ”. Ex: Change KTU7-D-2D-0.16-DG to KTU7-D-2D-0.16-DJ.
 ③ Load Terminal Cover KT7-PEFC is included with any factory modifications.

Enclosed KTU7 Circuit Breaker - Type 4 / 12

Fixed Thermal Current Rating [A]		Magnetic Trip [A]	Interrupting Rating (60Hz) [KA]			Catalog Number	Price	Dimension Code
			240V	480Y /277V	600Y /347V			
KTU7-D — High Interrupting Capacity – 2-Pole								
0.5	15...20xln	100	100	50	KTU7-D-2D-0.5-WG	875	W6 ①	
1.0	15...20xln	100	100	50	KTU7-D-2D-1-WG			
2.0	15...20xln	100	100	50	KTU7-D-2D-2-WG			
3.0	15...20xln	100	100	50	KTU7-D-2D-3-WG			
4.0	15...20xln	100	100	50	KTU7-D-2D-4-WG			
5.0	15...20xln	100	100	50	KTU7-D-2D-5-WG			
6.0	15...20xln	100	100	50	KTU7-D-2D-6-WG			
8.0	15...20xln	100	100	50	KTU7-D-2D-8-WG			
10.0	15...20xln	100	100	50	KTU7-D-2D-10-WG			
12.0	15...20xln	65	65	25	KTU7-D-2D-12-WG			
15.0	15...20xln	65	65	25	KTU7-D-2D-15-WG			
20.0	15...20xln	65	65	25	KTU7-D-2D-20-WG			
25.0	15...20xln	65	65	25	KTU7-D-2D-25-WG			
30.0	15...20xln	65	65	25	KTU7-D-2D-30-WG			
KTU7-D — High Interrupting Capacity – 3-Pole								
0.5	15...20xln	100	100	50	KTU7-D-3D-0.5-WG	975	W6 ①	
1.0	15...20xln	100	100	50	KTU7-D-3D-1-WG			
2.0	15...20xln	100	100	50	KTU7-D-3D-2-WG			
3.0	15...20xln	100	100	50	KTU7-D-3D-3-WG			
4.0	15...20xln	100	100	50	KTU7-D-3D-4-WG			
5.0	15...20xln	100	100	50	KTU7-D-3D-5-WG			
6.0	15...20xln	100	100	50	KTU7-D-3D-6-WG			
8.0	15...20xln	100	100	50	KTU7-D-3D-8-WG			
10.0	15...20xln	100	100	50	KTU7-D-3D-10-WG			
12.0	15...20xln	65	65	25	KTU7-D-3D-12-WG			
15.0	15...20xln	65	65	25	KTU7-D-3D-15-WG			
20.0	15...20xln	65	65	25	KTU7-D-3D-20-WG			
25.0	15...20xln	65	65	25	KTU7-D-3D-25-WG			
30.0	15...20xln	65	65	25	KTU7-D-3D-30-WG			

Painted Steel, Type 4 / 12 Enclosure



Includes:

- Type 4/12 enclosure – watertight, dusttight
- KTU7 UL489 Molded Case Circuit Breaker
- Black Type 4/4X/12; IP66 handle (Cat.# KT7-HTN Series E) ②

Modifications (Factory Assembled) ③

Description	Add Suffix to Cat. Number	Price Adder
KT7 Auxiliaries & Trip Contacts - Front Mount		
1 NO Auxiliary	-A10	60
1 NC Auxiliary	-A01	
1 NO + 1 NC Auxiliary	-A11	
2 NO Auxiliaries	-A20	
1 NO SC+OL + 1 NC Auxiliary	-T10A01	90
1 NO SC+OL + 1 NO Auxiliary	-T10A10	

① KTU7 up to 15 Amp is 100% rated in this enclosure. KTU7 20...30 Amp is 80% rated.
 ② A red and yellow handle may be selected instead of the standard black handle. Change "WG" suffix to "WJ". Ex: Change KTU7-D-2D-0.16-WG to KTU7-D-2D-0.16-WJ.
 ③ Load Terminal Cover KT7-PEFC is included with any factory modifications.